Support arms

The different types of support arms ensure a greater sense of security for both the independent user and the carer.

The support arms are manufactured with a Rilsan^{*}-coated surface which is comfortable to hold, easy to clean and protects against rust.

The support arms are supplied as fixed or height-adjustable models, and can be folded away when not in use.

Materials: Rilsan®-coated steel, pressure-cast aluminium, plastic

The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends.



Support arms for mounting on toilet

R1170000 R1171000

With toilet seat R37 Without toilet seat


Can be mounted easily and quickly on the toilet. The padded handles are comfortable for hands and arms. The support arms can be folded individually. Supplied with hinges BL1999. Only recommended for use with the following toilet seats: R26, R27, R28, R29, R30, R36, R37 or R38.

The support arms are suitable for people who need to be supported slightly when using the toilet. For people transferring from a wheelchair to the toilet, wall-mounted support arms are recommended.









R1110000 Height-adjustable, 150 mm

Support arm, height-adjustable - with leg

With leg, height-adjustable, 145 mm

Length: 850 mm Projection when folded: 200 mm Max. load: 120 kg Mounting kit for masonry walls included.









Support arm, height-adjustable - on free-standing floor column 0

R1161000 Height-adjustable, 670 mm

Length: 850 mm Max. load: 120 kg Mounting kit for floors included.

0

R1111000

Length: 850 mm

Max. load: 135 kg

Projection when folded: 155 mm


Mounting kit for masonry walls included.

- Suitable if:
- the wall is unstable
- the distance between the wall and the toilet is more than 700 mm
- wall mounting is not possible for any other reason.



R1100000 Support arm

Length: 850 mm Projection when folded: 185 mm Max. load: 120 kg Mounting kit for masonry walls included.





Height: 850 mm Height: 800 mm

Length: 850 mm Projection when folded: 140 mm Max. load: 135 kg Mounting kit for masonry walls included.